VARI-FOCAL CAMERA

DX-322CSVF
DX-372CSVF

* Functionality is subject to camera model



3 Axis
180° Tile Rotation
180° Pan Rotation
360° Horizontal Rotation

- Vari Focal 2.8-12/ 4~9mm lens
- 3 AXIS Mechanism
- Beautiful Design
- Friendly Installation
- IR CUT FILTER

DX-372CSVF

- Sony Effio-E
- 1/3" CCD 650 TVL
- 2D Noise Reduction
- OSD Menu
- Motion Detection and Privacy Masking
- Color Rolling Control
- BLC/HLC/AGC
- ATR (Adaptive Tone Reproduction)

DX-322CSVF

- 1/3 SONY CCD
- 420 TVL resolution
- Compact and Beautiful Design
- Auto White Balance

Specifications

MODEL	DX-372CSVF	DX-322CSVF
Image Sensor	1/3" Sony DS CCD (PAL:ICX673AK/NTSC:ICX672AK)	1/3" Sony CCD (PAL:ICX633BK/NTSC:ICX632BK)
DSP System	CXD4140	CXD3142
Effective Pixels	PAL:976(H)x582(V) NTSC:976(H)x494(V)	PAL:537(H)×597(V) NTSC:537(H)×505(V)
Scanning System	PAL/NTSC	
Horizontal Resolution	**650TVL**	**420TVL**
Min. Illumination	0.3 Lux / F1.0	0.5 LUX
OSD Menu	Available(7 languages)	Not Available
Backlight Compensation	BLC/HLC/OFF	Not Available
Sync. System	Internal	Internal
S/N Ratio	≥48db (AGC Off)	48db (AGC Off)
White Balance	Atw/Push/User/ Anti CR/Manual	Auto (AWB)
Gamma Correction	0.45	0.45
Gain Control	Yes	Auto (AGC)
Motion Detection	On/Off(4 Zone)	Not Available
Privacy Masking	On/Off(4 Zone)	Not Available
Mirror(H-REV)	On/Off	Not Available
SHARPNESS	On/Off (Level Adjutable)	Not Available
D/N Selection	Color/B/W/Auto	Not Available
ATR	On/Off	Not Available
Noise Reduce	2D-DNR	Not Available
Picture Adjustment	Yes	Not Available
Analog Output	Composite, BNC (1.0Vp-p.75hm)	
Lens	4-9mm/2.8-12mm	
Power	DC 12V / 150mA	
Dimension	127W x 88H mm	
Net Weight	280G	

Independent ceilling mount for fast and easy installation